

Fine Fissured

Mineral Fiber Ceilings







LEED® v4

- MR: Environmental Product Declarations (EPDs)
- MR: Sourcing Raw Materials
- MR: Material Ingredients (HPDs)
- IEQ: Daylight
- IEQ: Low-Emitting Materials
- IEQ: Prereq. Min. Acoustic Performance (Schools)
- IEQ: Acoustic Performance
- MR: PBT Source Reduction (Healthcare)
- IEQ: Interior Lighting
- EA: Prereq. Min. Energy Performance
- EA: Optimize Energy Performance
- Recycled Content CLASS A Pre: **33%** | Post: **0%** PROTECTONE® Pre: 45% | Post: 0%

TOOLS

Visit CertainTeed.com/Ceilings Download HPDs and EPDs LEED® Information / BIM Objects 3-Part Specs / Data Pages



Reduction Rapidly Renewable Resource Content Recycled Content



EPD Available



In addition to traditional white, you can make an impact with one of our 5 standard colors for item numbers HHF-154, HHF-157, HHF-197

Silver Lining

FEATURES & BENEFITS

- 100% non-directional pattern

Beige Breeze

- Available in fire-rated (Protectone®) versions
- Variety of edge detail options and panel sizes

Blondewood

- High humidity and sag resistant
- Third-party verified Environmental Product Declaration (EPD) available for this product
- Health Product Declaration (HPD) available for this product

APPLICATIONS

White Wash

- Schools

Wet Clay

- Libraries
- Retail / Department Stores
- Offices
- Other Commercial Buildings / Space Applications

AVAILABLE EDGE DETAILS





15/16 Grid



Corner Bevel

9/16 Grid



9/16 Grid Bolt Slot

Color-coordinated suspension systems available



Fine Fissured Reveal (White) (HHF-154)

ATTRIBUTES			*	<u> </u>	EPD	HPD	<u> </u>	1			*	LOW	4
	DIMENSIONS INCHES	EDGE DETAIL		LASSIFIED	EPD AVAILABLE	HPD AVAILABLE	SAG RESISTANT	MOLD RESISTANT	LR	WASHABLE	FIRE CLASS (ASTM E1264)	EMISSION COMPLIANT	RECYCLED CONTENT
FINE FISSURED													
HHF-157	24 x 24 x 5/8	Trim	0.55	33	Yes	Yes	Yes	BioShield	0.84	_	Class A	Certified	33%
PFF-157	24 x 24 x 5/8	Trim	0.55	35	Yes	Yes	Yes	BioShield	0.84	_	Protectone*	Certified	45%
HHF-154	24 x 24 x 5/8	Reveal	0.55	33	Yes	Yes	Yes	BioShield	0.84	_	Class A	Certified	33%
PFF-154	24 x 24 x 5/8	Reveal	0.55	35	Yes	Yes	Yes	BioShield	0.84	_	Protectone*	Certified	45%
HHF-150	24 x 24 x 5/8	Narrow Reveal	0.55	35	Yes	Yes	Yes	BioShield	0.84	_	Class A	Certified	33%
HHF-197	24 x 48 x 5/8	Trim	0.55	35	Yes	Yes	Yes	BioShield	0.84	_	Class A	Certified	33%
PFF-197	24 x 48 x 5/8	Trim	0.55	40	Yes	Yes	Yes	BioShield	0.84	_	Protectone*	Certified	45%
HHF-194	24 x 48 x 5/8	Reveal	0.55	35	Yes	Yes	Yes	BioShield	0.84	_	Class A	Certified	33%
HHF-2067	20 x 60 x 5/8	Trim	0.55	35	Yes	Yes	Yes	BioShield	0.84	_	Class A	Certified	33%
HHF-177	24 × 60 × 5/8	Trim	0.55	35	Yes	Yes	Yes	BioShield	0.84	_	Class A	Certified	33%
FINE FISSURED - METRIC													
HHF-2067M	500 x 1500 x 15	Trim	0.55	35	Yes	Yes	Yes	BioShield	0.84	_	Class A	Certified	33%

 $^{^{\}star}$ Protectone": A fire-resistive ceiling when used in applicable UL assemblies.

CAN'T FIND A SIZE? Contact your local Sales Representative or call 800-233-8990

PHYSICAL DATA

MATERIAL

Mineral Fiber

ASTM E1264 CLASSIFICATION

Type III, Form 2, Pattern C D

FIRE CLASS (ASTM E1264)

Tested according to ASTM E84 & CAN S102 Flame Spread: 25 or less Smoke Developed: 50 or less

VOC EMISSIONS

Independently certified compliant with California
Department of Public Health CDPH/EHLB/Standard Method Version 1.1, 2010.

MOLD/MILDEW RESISTANCE

BioShield® treatment included for added mold and mildew resistance.

MAINTENANCE

Wipe with a soft cloth or vacuum with brush attachment.

WARRANTY

15-Year Limited System Warranty

INSTALLATION CONSIDERATION

Colored ceilings are dye-lotted and should not be mixed.

