

PERFORMA®

School Board®
VOC Compliant



LOW
VOC

\$\$\$

LEED® v4

LEED® v4

● MR: Environmental Product Declarations (EPDs)

● MR: Sourcing Raw Materials

● MR: Material Ingredients (HPDs)

● IEQ: Daylight

● IEQ: Low-Emitting Materials

● IEQ: Prereq. Min. Acoustic Performance (Schools)

● IEQ: Acoustic Performance

● MR: PBT Source Reduction (Healthcare)

● IEQ: Interior Lighting

● EA: Prereq. Min. Energy Performance

● EA: Optimize Energy Performance

● Recycled Content
CLASS A Pre: **33%** Post: **0%**
PROTECTONE® Pre: **45%** Post: **0%**

TOOLS

Visit CertainTeed.com/Ceilings
Download HPDs and EPDs
LEED® Information / BIM Objects
3-Part Specs / Data Pages



Carbon Footprint Reduction
Rapidly Renewable Resource Content
Recycled Content



EPD Available



HPD Available

FEATURES & BENEFITS

- Up to 25% higher surface hardness than conventional wet-felted ceiling products per ASTM C 367 testing
- Third-party verified Environmental Product Declaration (EPD) available for this product
- Available in fire-rated (Protectone®) versions
- Shares surface pattern with other Fine Fissured products
- Health Product Declaration (HPD) available for this product

APPLICATIONS

- Schools
- Day Care Centers
- Corridors
- Commercial Interior Spaces
- Dorms
- Other Commercial Buildings / Space Applications

AVAILABLE EDGE DETAILS



Trim
15/16 Grid



School Board® Trim (PFFSB-197)

ATTRIBUTES

	DIMENSIONS (INCHES)	EDGE DETAIL	UL CLASSIFIED NRC	CAC	EPD AVAILABLE	HPD AVAILABLE	SAG RESISTANT	MOLD RESISTANT	LR	WASHABLE	FIRE CLASS (ASTM E1264)	EMISSION COMPLIANT	RECYCLED CONTENT
SCHOOL BOARD®													
FFSB-157	24 x 24 x 5/8	Trim	0.55	35	Yes	Yes	Yes	BioShield	0.84	—	Class A	Certified	33%
PFFSB-157	24 x 24 x 5/8	Trim	0.55	35	Yes	Yes	Yes	BioShield	0.84	—	Protectone*	Certified	45%
FFSB-197	24 x 48 x 5/8	Trim	0.55	35	Yes	Yes	Yes	BioShield	0.84	—	Class A	Certified	33%
PFFSB-197	24 x 48 x 5/8	Trim	0.55	40	Yes	Yes	Yes	BioShield	0.84	—	Protectone*	Certified	45%

Protectone: A fire-resistive ceiling when used in applicable UL assemblies.

CAN'T FIND A SIZE? Contact your local Sales Representative or call 800-233-8990

PHYSICAL DATA

MATERIAL

Mineral Fiber

ASTM E1264 CLASSIFICATION

Type III, Form 2, Pattern C D

FIRE CLASS (ASTM E1264)

Tested according to ASTM E84 & CAN S102
Flame Spread: 25 or less
Smoke Developed: 50 or less

VOC EMISSIONS

Independently certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.1, 2010.

MOLD/MILDEW RESISTANCE

BioShield® treatment included for added mold and mildew resistance.

MAINTENANCE

Wipe with a soft cloth or vacuum with brush attachment.

WARRANTY

10-year 104/90 Limited Warranty

Technical Support | certainteed.com/ceilings 800-233-8990

© 01/17 CertainTeed Corporation

CertainTeed
SAINT-GOBAIN
Ceilings