

**Cashmere®**  
Mineral Fiber Ceilings



In addition to traditional white, you can make an impact with one of our 5 standard colors for item numbers CM-450, CM-454



Beige Breeze      Blondewood      Silver Lining      Wet Clay      White Wash

**FEATURES & BENEFITS**

- Upscale appearance
- Finely textured
- Available in fire-rated (Protectone®) versions
- Third-party verified Environmental Product Declaration (EPD) available for this product
- Health Product Declaration (HPD) available for this product

**APPLICATIONS**

- Offices
- Healthcare Areas
- Retail / Department Stores
- Hospitality Areas
- Other Commercial Buildings / Space Applications

LOW VOC



**LEED® v4**

● MR: Environmental Product Declarations (EPDs)

● MR: Sourcing Raw Materials

● MR: Material Ingredients (HPDs)

● IEQ: Daylight

● IEQ: Low-Emitting Materials

● IEQ: Prereq. Min. Acoustic Performance (Schools)

● IEQ: Acoustic Performance

● MR: PBT Source Reduction (Healthcare)

● IEQ: Interior Lighting

● EA: Prereq. Min. Energy Performance

● EA: Optimize Energy Performance

● Recycled Content  
CLASS A Pre: **57%** Post: **1%**  
PROTECTONE® Pre: **37%** Post: **1%**

**TOOLS**

Visit [CertainTeed.com/Ceilings](http://CertainTeed.com/Ceilings)  
Download HPDs and EPDs  
LEED® Information / BIM Objects  
3-Part Specs / Data Pages



Carbon Footprint Reduction  
Rapidly Renewable Resource Content  
Recycled Content




EPD Available




HPD Available


**AVAILABLE EDGE DETAILS**




Trim  
15/16 Grid



Reveal  
Beveled  
15/16 Grid



Narrow Reveal  
Corner Bevel  
9/16 Grid



Narrow Reveal  
Corner Bevel  
9/16 Grid Bolt Slot

Color-coordinated suspension systems available



Cashmere® Narrow Reveal (White) (CM-450)

## ATTRIBUTES

	DIMENSIONS (INCHES)	EDGE DETAIL	UL CLASSIFIED NRC	CAC	EPD AVAILABLE	HPD AVAILABLE	SAG RESISTANT	MOLD RESISTANT	LR	WASHABLE	FIRE CLASS (ASTM E1264)	EMISSION COMPLIANT	RECYCLED CONTENT
<b>CASHMERE®</b>													
<b>CM-457</b>	24 x 24 x 3/4	Trim	0.60	35	Yes	Yes	Yes	BioShield	0.83	—	Class A	Certified	58%
<b>CM-454</b>	24 x 24 x 3/4	Reveal	0.60	35	Yes	Yes	Yes	BioShield	0.83	—	Class A	Certified	58%
<b>PCM-454</b>	24 x 24 x 3/4	Reveal	0.45	35	Yes	Yes	Yes	BioShield	0.83	—	Protectone*	Certified	38%
<b>CM-450</b>	24 x 24 x 3/4	Narrow Reveal	0.60	35	Yes	Yes	Yes	BioShield	0.83	—	Class A	Certified	58%
<b>PCM-450</b>	24 x 24 x 3/4	Narrow Reveal	0.45	35	Yes	Yes	Yes	BioShield	0.83	—	Protectone*	Certified	38%
<b>CM-497</b>	24 x 48 x 3/4	Trim	0.60	35	Yes	Yes	Yes	BioShield	0.83	—	Class A	Certified	58%
<b>CM-494</b>	24 x 48 x 3/4	Reveal	0.60	35	Yes	Yes	Yes	BioShield	0.83	—	Class A	Certified	58%
<b>CM-490</b>	24 x 48 x 3/4	Narrow Reveal	0.60	35	Yes	Yes	Yes	BioShield	0.83	—	Class A	Certified	58%

\*Protectone®: A fire-resistive ceiling when used in applicable UL assemblies.

**CAN'T FIND A SIZE?** Contact your local Sales Representative or call 800-233-8990

## PHYSICAL DATA

**MATERIAL**  
Mineral Fiber

**ASTM E1264 CLASSIFICATION**  
Type III, Form 2, Pattern E

**FIRE CLASS (ASTM E1264)**  
Tested according to ASTM E84 & CAN S102  
Flame Spread: 25 or less  
Smoke Developed: 50 or less

**VOC EMISSIONS**  
Independently certified compliant with California  
Department of Public Health CDPH/EHLB/Standard  
Method Version 1.1, 2010.

**MOLD/MILDEW RESISTANCE**  
BioShield® treatment included for added mold and  
mildew resistance.

**MAINTENANCE**  
Wipe with a soft cloth or vacuum with brush attachment.

**WARRANTY**  
10-year 104/90 Limited Warranty

**INSTALLATION CONSIDERATION**  
Colored ceilings are dye-lotted and should not be mixed.